

Technical data sheet

VISIO 2 L

OPTIONS

Support frame	
Black, 6mm	✓
Window frame	
Black	✓
Handles	
Oak wood handle dark stained	✓
Stainless steel	✓
Steel black	✓
Air-system	
for room air independent installation	✓
Heat-storage module©	
Heat-storage module©	112 kg



Technical data sheet

VISIO 2 L

PRODUCT INFORMATION

Weight depending on model/equipment	
Weight depending on model/equipment	353 - 465 kg
Ø Smoke outlet	
Ø Smoke outlet	200 mm
Ø Air inlet	
Ø Air inlet	150 mm
Certifications	
Energy efficiency class	A+
Eco Design	✓
European standard	EN 16510
BlmSchV	Stufe 2
Flamme Verte	✓

Technical data sheet

VISIO 2 L

SERVICES

Thermal output	
Nominal heat output	11.9 kW
Fuelwood requirement	3.5 ≈ kg/h
Energy efficiency	≥75 %
Combustion air requirement	34.5 m ³ /h
Triple values	
Exhaust gas mass flow	11.6 g/s
Exhaust temperature	283 °C
Minimum flue draught	-12 Pa
Fire safety	
Dust at 13 % O ₂	≤40 mg/Nm ³
CO emission at 13 % O ₂	≤0.12 %
CO emission at 13 % O ₂	≤1500 mg/Nm ³
OGC at 13 % O ₂	≤120 mg/Nm ³
NO _x at 13 % O ₂	≤200 mg/Nm ³

INSTALLATION

Furniture distance from the front glass	
A: Furniture distance from the front glass	1250 mm
Furniture distance from the side glass	
B: Furniture distance from the side glass	800 mm

Technical data sheet

VISIO 2 L

Safety distances:

Information on safety distances can be found in the installation manual.

Note:

Maximum weight supported by the frame: 200 kg.