

# Technical data sheet

## VISIO 3

200



### OPTIONS

|                                       |       |
|---------------------------------------|-------|
| Support frame                         |       |
| Black, 6mm                            | ✓     |
| Stainless steel, 6mm                  | ✓     |
| Window frame                          |       |
| Black                                 | ✓     |
| Stainless steel                       | ✓     |
| Handles                               |       |
| Oak wood handle dark stained          | ✓     |
| Stainless steel                       | ✓     |
| Steel black                           | ✓     |
| AIR-System                            |       |
| for room air independent installation | ✓     |
| Heat-storage module©                  |       |
| Heat-storage module©                  | 42 kg |



200



# Technical data sheet

## VISIO 3



### PRODUCT INFORMATION

|                                     |              |
|-------------------------------------|--------------|
| Weight depending on model/equipment |              |
| Weight depending on model/equipment | 233 - 275 kg |
| Ø Smoke outlet                      |              |
| Ø Smoke outlet                      | 200 mm       |
| Ø Air inlet                         |              |
| Ø Air inlet                         | 150 mm       |
| Certifications                      |              |
| Energy efficiency class             | A            |
| Eco Design                          | ✓            |
| EN Norm 6.4.23                      | EN 13229     |
| BImSchV                             | Stufe 2      |
| Flamme Verte                        | ✓            |
| Classe energetica di appartenenza   | 4 Stelle     |



# Technical data sheet

## VISIO 3

200



### SERVICES

| Thermal output  |                         |
|---|-------------------------|
| Nominal heat output   | 7 kW                    |
| Thermal output range min./max.                                  | 5-9 kW                  |
| Fuelwood requirement  | 2 ≈ kg/h                |
| Energy efficiency   | 80 %                    |
| Triple values   |                         |
| Exhaust gas mass flow   | 7.5 g/s                 |
| Exhaust temperature   | 243 °C                  |
| Required delivery pressure                                      | 12 Pa                   |
| Required delivery pressure at 0.8 times the nominal heat output | 10 Pa                   |
| Fire safety   |                         |
| Dust at 13 % O <sub>2</sub>                                     | 5 mg/Nm <sup>3</sup>    |
| CO emission at 13 % O <sub>2</sub>                              | 0.09 %                  |
| CO emission at 13 % O <sub>2</sub>                              | 1150 mg/Nm <sup>3</sup> |
| CO <sub>2</sub> concentration                                   | 8.9 %                   |
| OGC at 13 % O <sub>2</sub>                                      | 45 mg/Nm <sup>3</sup>   |
| NO <sub>x</sub> at 13 % O <sub>2</sub>                          | 81 mg/Nm <sup>3</sup>   |

### INSTALLATION

| Furniture distance from the front glass    |         |
|--|---------|
| A: Furniture distance from the front glass | 1200 mm |
| Furniture distance from the side glass     |         |
| B: Furniture distance from the side glass  | 750 mm  |

All information is provided without guarantee. Sketches are not true to scale.

24.04.2026 | 3 / 4

ATTIKA FEUER AG | Brunnmatt 16 | CH-6330 Cham | Tel. +41 41 784 80 80 | info@attika.ch | www.attika.ch

200



# Technical data sheet

## VISIO 3



### CONVECTION AIR

|                      |                          |
|----------------------|--------------------------|
| Convection air above | min. 600 cm <sup>2</sup> |
| Convection air below | min. 400 cm <sup>2</sup> |

### Note

Maximum weight supported by the frame: 200 kg.

### Installation

